

Olympus 190 Tower Configuration

Model	Description	Dimensions (W x H x D)	Weight	Power
CLV-190	EVIS EXERA III XENON LIGHT SOURCE	370 x 150 x 476 mm (standard) 390 x 162 x 551 mm (maximum)	19 kg	100–240 V AC; within ±10%
CV-190	EVIS EXERA III VIDEO SYSTEM CENTER	370 x 85 x 455 mm; 382 x 91 x 489 mm (maximum)	10.7 kg	100-240 V AC (NTSC)/220-240 V AC (PAL); within ±10%
3DV-190	3D VISUALIZATION UNIT	370 x 85 x 454 mm; 375 x 91 x 478 mm (maximum)	7.7 kg	220–240 V AC; within ±10%
IMH-20	Image Management Hub	370 x 167.5 x 413 mm	10.7 kg	
ESG-400	Electrosurgical Generator	370 x 465 x 156 mm	12.5 kg	100 to 120 V~ / 220 to 240 V~
nStream® GX	HD Video and Image Capture	8.64 cm x 37.08 cm x 32.5 cm	4.53 KG	100-240 VAC
UHI-4	45L HIGH FLOW INSUFFLATION UNIT	370 X 120 X 300 MM	9.3 KG	100-240V
OEP-5	COLOR VIDEO PRINTER	280 x 125 x 398 mm	9 kg	100 – 120 V AC ±10% 50/60 Hz
OEV-262H	HIGH DEFINITION LCD MONITOR	626.8 (W) x 395.2 (H) x 79.6 (D) mm	7.8 kg	AC IN : 100-240 V, 50/60 Hz, 0.96-0.47 A DC IN : 24 V, 3.6 A, 5 V, 0.03 A